



**Driver incl.**

**CRI>80**

**blendfrei**

Art. Nr.	Bezeichnung	Lichtfarbe	Abmessungen (mm)	Lochmaß (mm)	Leistung (Watt)	Lumen	Chip Typ	Anzahl LED's
AL-030127	Downlight rund	2700K	85x15	70	3	165	2835	15
AL-030128	Downlight rund	3000 K	85x15	70	3	165	2835	15
AL-030128	Downlight rund	4000 K	85x15	70	3	165	2835	15
AL-030129	Downlight rund	2700K	120x15	105	6	330	2835	30
AL-030129	Downlight rund	3000K	120x15	105	6	330	2835	30
AL-030130	Downlight rund	4000K	120x15	105	6	330	2835	30
AL-030131	Downlight rund	2700K	170x15	155	12	780	2835	60
AL-030131	Downlight rund	3000K	170x15	155	12	780	2835	60
AL-030132	Downlight rund	4000K	170x15	155	12	780	2835	60
AL-030133	Downlight rund	2700K	225x15	210	18	1260	2835	91
AL-030133	Downlight rund	3000K	225x15	210	18	1260	2835	91
AL-030134	Downlight rund	4000K	225x15	210	18	1260	2835	91
AL-030135	Downlight rund	2700K	300x15	285	24	1680	2835	120
AL-030135	Downlight rund	3000K	300x15	285	24	1680	2835	120
AL-030136	Downlight rund	4000K	300x15	285	24	1680	2835	120

Garantie 3 Jahre

Abstrahlwinkel 100°±5°

IP-Klasse IP20

Dimmbarkeit optional

Spannung AC220-240V

Betriebsfenster -20 bis +40°C

Optik matt

Zertifikate CE; ISO 9001; ISO 14001; RoHS 2011/65/EU; LVD 2006/95/EC; EMC 2004/108/EC

Technische Änderungen und Irrtümer vorbehalten.